



	ACO	N	DMM	Q	UNIT	CAZOTC
					(mm)	(cm)
50	60	1	5.0	667	542.9	213.7
		2	5.0	4	168	67.2
		3	5.0	4	168	67.2
		4	5.0	6	180	71.1
		5	6.0	26	119	30.4
		6	6.0	26	119	30.4
		7	6.0	26	119	30.4
		8	6.0	4	466	184.4
		9	6.0	4	466	184.4
		10	6.0	4	466	184.4
	11	8.0	2	502	201.4	
	12	8.0	2	502	201.4	
	13	8.0	2	502	201.4	
	14	8.0	2	504	204.4	
	15	8.0	6	194	77.4	
	16	8.0	6	194	77.4	
	17	8.0	2	506	203.2	
	18	8.0	2	455	181.0	
	19	8.0	2	455	181.0	
	20	8.0	2	455	181.0	
	21	8.0	2	468	187.8	
	22	8.0	2	468	187.8	
	23	8.0	2	470	190.4	
	24	8.0	2	470	190.4	
	25	8.0	2	135	53.0	
	26	8.0	2	1144	458.8	
	27	8.0	6	1151	460.6	
	28	8.0	6	1151	460.6	
	29	8.0	4	79	31.8	
	30	8.0	4	79	31.8	
	31	8.0	4	465	182.4	
	32	8.0	4	465	182.4	
	33	8.0	4	465	182.4	
	34	8.0	4	465	182.4	
	35	8.0	1	207	82.0	
	36	8.0	1	207	82.0	
	37	8.0	2	137	53.0	
	38	8.0	2	137	53.0	
	39	8.0	2	137	53.0	
	40	10.0	2	31	12.2	
					182	71.8

	DIAM	C.TOTAL (m)	PESO+10% (kg)
CA50	8,0	538,7	234,2
CA60	10,0	17,9	12,1
PESO TOTAL	5,0	626,4	106,1
CA50	246,3		
CA60	106,1		

Vol. de concreto total (C-25) = 5.79 m³
Área de forma total = 100.50 m²

[illegible]